


Features

- 1 Pole - Low profile (15.4 mm height)
- 43.41 - 1 Pole, 10 A (3.2 mm pin pitch)
- 43.41-0300 - 1 Pole NO, 10 A (5 mm pin pitch)
- 43.61-0300 - 1 Pole NO, 16 A (5 mm pin pitch)
- PCB mount - direct or via PCB socket (43.41 version)

- Sensitive DC coil:
 - 250 mW (10 A version)
 - 400 mW (16 A version)
- Very high coil-contact isolation 10 mm, 6 kV (1.2/50 μ s)
- Cadmium Free contacts (preferred version)
- Flux proof: RT II standard, (RT III option)



FOR UL HORSEPOWER AND PILOT DUTY RATINGS
SEE "General technical information" page V

43.41



- 3.2 mm contact pin pitch
- 1 Pole CO, 10 A
- PCB direct or via socket

43.41-0300




- 5 mm contact pin pitch
- 1 Pole NO, 10 A
- PCB mount


43.61-0300




- 5 mm contact pin pitch
- 1 Pole NO, 16 A
- PCB mount



Copper side view



Copper side view



Copper side view

Contact specification				
Contact configuration		1 CO (SPDT)	1 NO (SPST-NO)	1 NO (SPST-NO)
Rated current/Maximum peak current	A	10/15	10/15	16/25
Rated voltage/Maximum switching voltage V AC		250/400	250/400	250/400
Rated load AC1	VA	2,500	2,500	4,000
Rated load AC15 (230 V AC)	VA	500	500	750
Single phase motor rating (230 V AC)	kW	—	—	—
Breaking capacity DC1: 30/110/220 V	A	10/0.3/0.12	10/0.3/0.12	16/0.3/0.12
Minimum switching load	mW (V/mA)	300 (5/5)	300 (5/5)	300 (5/5)
Standard contact material		AgNi	AgNi	AgNi
Coil specification				
Nominal voltage (U _N)	V AC (50/60 Hz)	—	—	—
	V DC	3 - 6 - 9 - 12 - 18 - 24 - 36 - 48	3 - 6 - 9 - 12 - 18 - 24 - 36 - 48	12 - 24 - 48
Rated power AC/DC	VA (50 Hz)/W	—/0.25	—/0.25	—/0.4
Operating range	AC	—	—	—
	DC	(0.7...1.5)U _N	(0.7...1.5)U _N	(0.7...1.2)U _N
Holding voltage	AC/DC	—/0.4 U _N	—/0.4 U _N	—/0.4 U _N
Must drop-out voltage	AC/DC	—/0.05 U _N	—/0.05 U _N	—/0.05 U _N
Technical data				
Mechanical life AC/DC	cycles	—/10 · 10 ⁶	—/10 · 10 ⁶	—/10 · 10 ⁶
Electrical life at rated load AC1	cycles	100 · 10 ³	100 · 10 ³	50 · 10 ³
Operate/release time	ms	6/4	6/2	6/2
Insulation between coil and contacts (1.2/50 μ s)	kV	6 (10 mm)	6 (10 mm)	6 (10 mm)
Dielectric strength between open contacts V AC		1,000	1,000	1,000
Ambient temperature range	°C	—40...+85	—40...+85	—40...+85
Environmental protection		RT II	RT II	RT II
Approvals (according to type)				

Ordering information

Example: 43 series low-profile PCB relay, 1 CO (SPDT), 24 V DC coil.

<div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">4</div> <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">3</div> . <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">4</div> . <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">1</div> . <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">7</div> . <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">0</div> <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">2</div> <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">4</div> . <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">2</div> <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">0</div> <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">0</div> <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 2px;">0</div>	<p>Series</p> <p>Type 4 = PCB - 3.2 mm pinning (CO/SPDT, 10 A) PCB - 5 mm pinning (NO/SPST-NO, 10 A) 6 = PCB - 5 mm pinning (NO/SPST-NO, 16 A)</p> <p>No. of poles 1 = 1 pole</p> <p>Coil version 7 = Sensitive DC (only for 43.41) 9 = DC (only for 43.61)</p> <p>Coil voltage See coil specifications</p>	<p>A: Contact material 0 = AgNi 2 = AgCdO 4 = AgSnO₂ 5 = AgNi + Au (5 μm)</p> <p>B: Contact circuit 0 = CO (SPDT) - (for 43.41 only) 3 = NO (SPST)</p>	<p>C: Options 0 = None</p> <p>D: Special versions 0 = Flux proof (RT II) 1 = Wash tight (RT III)</p>
--	---	---	---

Selecting features and options: only combinations in the same row are possible.
 Preferred selections for best availability are shown in **bold**.


Type	Coil version	A	B	C	D
43.41	sensitive DC	0 - 2 - 4 - 5	0 - 3	0	0 - 1
43.61	DC	0 - 2 - 4	3	0	0

Technical data


Insulation according to EN 61810-1			
Nominal voltage of supply system	V AC	230/400	
Rated insulation voltage	V AC	250	400
Pollution degree		3	2
Insulation between coil and contact set			
Type of insulation		Reinforced (10 mm)	
Overvoltage category		III	
Rated impulse voltage	kV (1.2/50 μs)	6	
Dielectric strength	V AC	4,000	
Insulation between open contacts			
Type of disconnection		Micro-disconnection	
Dielectric strength	V AC/kV (1.2/50 μs)	1,000/1.5	
Conducted disturbance immunity			
Burst (5...50)ns, 5 kHz, on A1 - A2		EN 61000-4-4	level 4 (4 kV)
Surge (1.2/50 μs) on A1 - A2 (differential mode)		EN 61000-4-5	level 3 (2 kV)
Other data			
Bounce time: NO/NC	ms	3/6	
Vibration resistance (5...55)Hz: NO/NC	g	15/3	
Shock resistance	g	15	
Power lost to the environment	without contact current	W	0.25 (43.41) 0.4 (43.61)
	with rated current	W	1.3 (43.41) 2 (43.61)
Recommended distance between relays mounted on PCB	mm	≥ 5	

Contact specification

F 43 - Electrical life (AC) v contact current



H 43 - Maximum DC1 breaking capacity




- When switching a resistive load (DC1) having voltage and current values under the curve, an electrical life of $\geq 100 \cdot 10^3$ for 43.41 and $\geq 50 \cdot 10^3$ for 43.61 can be expected.
- In the case of DC13 loads, the connection of a diode in parallel with the load will permit a similar electrical life as for a DC1 load.
Note: the release time for the load will be increased.

Coil specifications

DC coil data - 0.25 W sensitive (type 43.41)

Nominal voltage U_N V	Coil code	Operating range		Resistance R Ω	Rated coil consumption I at U_N mA
		U_{min} V	U_{max} V		
3	7.003	2.2	4.5	36	83.5
6	7.006	4.2	9	150	40
9	7.009	6.5	13.5	324	27.7
12	7.012	8.4	18	580	20.7
18	7.018	13	27	1,300	13.8
24	7.024	16.8	36	2,200	10.9
36	7.036	25.2	54	5,200	6.9
48	7.048	33.6	72	9,200	5.2

R 43 - DC coil operating range v ambient temperature



- 1 - Max. permitted coil voltage.
2 - Min. pick-up voltage with coil at ambient temperature.

DC coil data - 0.4 W standard (type 43.61)

Nominal voltage U_N V	Coil code	Operating range		Resistance R Ω	Rated coil consumption I at U_N mA
		U_{min} V	U_{max} V		
12	9.012	8.4	14.4	360	33.3
24	9.024	16.8	28.8	1,400	17.1
48	9.048	33.6	57.6	5,760	8.3